

BRASS PNEUMATIC REPLACEMENT TIRE - SF



- Shiny brass hub.
- Black or Gray Pneumatic tires feature non-marking floor protection.
- Full pneumatics cushion the load on air, just like an automobile tire.
- Smoother ride over rough floors.
- Wheels can be filled with urethane foam to make them deflation proof, but foam has no effect on capacity.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number
Black Tread							
8	2.50/4	210	2-7/16	1-3/8	1/2	3	SF084270805
Grey Tread							
8	2.50/4	210	2-7/16	1-3/8	1/2	3	SF084270806

PNEUMATIC HAND TRUCK WHEELS - SO

Capacity Up to 350 lbs.



Dia. (inch)	Width (inch)	Capacity (lbs)	Ply Rating	Hub Length	Air Pressure	Bearing (inch)	Wt. (lbs)	Part Number
10.5	4.10/4	350	4	2-1/4	50	5/8	2	SF1062710

Roller Bearing (01), Tapered Bearing (09), Ball Bearing (27)

Hand Truck Wheel (SO) This 4-ply rating tire with offset hub is the perfect answer for all your hand truck replacement needs.

SEMI-PNEUMATIC HAND TRUCK WHEELS - SN

Capacity Up to 540 lbs.



Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Part Number
6.2	2.00EHS	200	2-1/4	3/4	3	SN/HT0620112
6.2	2.00EHS	200	2-1/2	1/2	3	SN/HT0622708
8.6	2.50EHS	350	3	3/4	5-3/4	SN/HT0840112
8.6	2.50EHS	350	3	1/2	5-3/4	SN/HT0842708
10.0	2.75EHS	350	3-1/4	3/4	7-1/4	SN/HT1040112
10.0	2.75EHS	350	3-1/4	1/2	7-1/4	SN/HT1042708
12.1	3.00EHS	540	3-1/2	3/4	13-1/2	SN/HT1250112
12.1	3.00EHS	540	3-1/2	1/2	13-1/2	SN/HT1252708

Roller Bearing (01), Ball Bearing (27)

Semi-Pneumatic (SN/HT) These shock absorbing pneumatic wheels have no inflation problems, because they are not pressurized. All bearings are pressure lubricated, except the 6" diameter wheels, which must be lubricated through the hollow axle.