

ELASTIC RUBBER/ ALUMINUM - ERB

Capacity Up to 880 lbs.



Super elastic rubber tread wheels with precision ball bearings are rapidly replacing moldon rubber tread wheels. Vulcanized, for non-detachable bond, higher loading, smoother riding, low rolling resistance and are non-marking.

Features

- **Wheel face:** Moderate crown.
- **Finish:** Blue tread on aluminum core.
- **Temperature Range:** -40°F up to +180°F.
- **Hardness:** 65 Shore A.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number*
6	2	660	2-7/16	1-3/16	1/2	3	ERB08229-06
8	2	880	2-7/16	1-3/16	1/2	4	ERB08229-08

Complete with Top Hat Bushings and Centerpiece

ELASTIC RUBBER SOLID/ALUMINUM



SERIES ERS

SERIES ERN

ELASTIC solid rubber wheels

Aluminum rim with securely vulcanized ELASTIC solid rubber tire with ball bearings (/5).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
ERN/100/040/5/15	100	40	45	45	15	160
ERN/125/040/5/15	125	40	45	45	15	180
ERN/125/050/5/20	125	50	54	60	20	225
ERN/125/050/5/25	125	50	54	60	25	225
ERN/160/050/5/20	160	50	54	60	20	300
ERN/160/050/5/25	160	50	54	60	25	300
ERN/180/050/5/20	180	50	54	60	20	350
ERN/180/050/5/25	180	50	54	60	25	350
ERN/200/050/5/20-1	200	50	54	54	20	400
ERN/200/050/5/20-2	200	50	54	60	20	400
ERN/200/050/5/25	200	50	54	60	25	400
ERN/250/050/5/20	250	50	54	60	20	500
ERN/250/050/5/25	250	50	54	60	25	500
ERN/300/060/5/30-1	300	60	54	60	30	650
ERN/300/060/5/30-2	300	60	75	74	30	650

25.4 mm = 1 inch 1 kg = 2.2 lbs

All wheels can fit in U.S. caster rigs.

ELASTIC solid rubber wheels

Highly stable pressed steel rim with securely vulcanized ELASTIC solid rubber tire with ball bearings (/5).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
ERS/160/050/5/25	160	50	50	50	25	350
ERS/200/050/5/25	200	50	50	50	25	400
ERS/200/080/5/30	200	80	80	80	30	600
ERS/250/050/5/25	250	50	50	50	25	400
ERS/250/060/5/30	250	60	60	60	30	500
ERS/250/080/5/30	250	80	80	80	30	700
ERS/300/075/5/30	300	75	75	75	30	800

25.4 mm = 1 inch 1 kg = 2.2 lbs

All wheels can fit in U.S. caster rigs.