

3,000 LBS. LOAD CAPACITY STAINLESS STEEL KINGPINLESS TYPE CASTERS

- **Top Plate:** 5/16" 304 stainless steel welded inside and out to 316 stainless steel raceway for longer life.
- **Swivel Section:** One row of 1/2" ball bearings mounted in a precision machined raceway. Zerk in swivel section.
- **Yoke Base:** Notched 316 stainless steel.
- **Legs:** 304 stainless steel welded inside and out.
- **Axle:** 3/4" diameter.
- Alternate or custom caster configurations available.

BRAKES OPTIONS



Poly Cam
specify **P**



Single Sided specify **SSB310**
Double Sided specify **DSB310**



Face Contact
specify **FBB**



Hand Operated Swivel Lock
specify **SL3000000**



TOE GUARDS AVAILABLE WITH ALL CASTERS.

Designed from premium grade 304 stainless steel caster rig with a strong premium 316 stainless swivel section. Excellent finish to protect caster from cleaning agents, steam, caustic solutions, or other corrosive agents which can cause rust.

TYPICAL APPLICATIONS

- Conveyor-drawn tow-trucks
- Heavy duty bakery racks
- Production dollies
- Heavy duty dough troughs

MOUNTING PLATE OPTIONS

TOP PLATE: (STANDARD)

Plate Size: 4-1/2 X 6-1/4
Bolt Holes: 2-7/16 x 4-15/16
slotted to
3-3/8 x 5-1/4
Bolt Size: 1/2

TOP PLATE: D

Plate Size: 5 x 5-1/2
Bolt Holes: 4-1/8 x 4-1/2
Bolt Size: 3/8

BEARING OPTIONS


Straight Roller **(01)**
Precision Ball **(28)**

*Add options to end of part number.

**NYLACRON™
CAST NYLON
28 PRECISION BEARING
NY/MD**

FOR MONOCAST
MC/MD

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
GRDUSS63NYMD	GRDUSR63NYMD	6	3	3000	7-1/2	1-3/8
GRDUSS83NYMD	GRDUSR83NYMD	8	3	3000	10-1/8	2-1/16
GRDUSS103NYMD	GRDUSR103NYMD	10	3	3000	11-1/2	2-1/4
GRDUSS123NYMD	GRDUSR123NYMD	12	3	3000	13-1/2	2-11/16



**X-TREME
PLUS SOLID POLYURETHANE
28 PRECISION BEARING
XP**

• Prevenz™ antimicrobial models available

• Add PREV to end of caster number

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
GRDUSS83XP	GRDUSSR83XP	8	3	2000	10-1/8	2-1/16
GRDUSS103XP	GRDUSSR103XP	10	3	2500	11-1/2	2-1/4



**PHENOLIC
01 ROLLER BEARING
TM**

• Prevenz™ antimicrobial models available

• Add PREV to end of caster number

• Tapered Roller 09 Bearings available

• Change "01" to "09"
Example: 6KSSS63TM09

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
GRDUSS63TM	GRDUSSR63TM	6	3	2000	7-1/2	1-3/8
GRDUSS83TM	GRDUSSR83TM	8	3	2500	10-1/8	2-1/16
GRDUSS103TM	GRDUSSR103TM	10	3	2900	11-1/2	2-1/4
GRDUSS123TM	GRDUSSR123TM	12	3	3000	13-1/2	2-11/16



MEGALOAD™ AND VULKOLLAN™ WHEELS WITH PRECISION BALL BEARINGS AVAILABLE TO FIT THIS CASTER SERIES.

SIZES 6 X 3, 8 X 3, 10 X 3 & 12 X 3.