

HIGH-TEMP PHENOLIC - HT

Capacity Up to 2600 lbs.



Features

- Phenolic resin mixed with macerated canvas made for high temperature applications best suited for dry heat (powder coating, bakeries, etc).
- Exceptional resistance to oil, grease, and most acids, chemicals and cleaning solutions.
- Hard tread rolls exceptionally easy; not recommended for rough surfaces.
- Durometer: 95 Shore D +/-5.
- Temperature range: -40°F to +475°F. continuous, 550°F intermittent.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Roller Bearings*	Part Number
4	2	2-3/16	600	02, 04, 05, 09, 92	HT40JQ*
5	2	2-3/16	750	02, 04, 05, 09, 92	HT50JQ*
6	2	2-3/16	900	02, 04, 05, 09, 92	HT60JQ*
8	2	2-3/16	1100	02, 04, 05, 09, 92	HT80JQ*
8	3	3-1/4	1900	24, 26	HT80LQ*
10	3	3-1/4	2400	24, 26	HT10LQ*
12	3	3-1/4	2600	24, 26	HT12LQ*

Replace* with desired bearing code.

02 Roller bearing ID 5/8", 04 Roller bearing ID 3/4",

05 SS Roller bearing ID 3/4", 09 Caged roller bearing ID 3/4"

92 I.D. 3/4" Roller bearing w/stl. bushing 1/2" inner diameter

24 Roller bearing ID 1", 26 Roller bearing ID 1-3/4"