

NYLON/GLASS-FILLED NG

Capacity Up to 1400 lbs.



Features

- **Wheel face:** Slight crown.
- **Finish:** Black.
- **Temperature Range:** -40° to +250°F.
- **Hardness:** 85 Shore D ±5.
- **Won't absorb moisture!**

Dia. (inch)	Width (in)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number*
4	2	800	2-3/16	1-3/16	1/2	1	NG0422908
5	2	1000	2-3/16	1-3/16	1/2	1	NG0522908
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	NG0622908
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	NG0822908

*Available with Stainless Steel Bearings (29SS)

*Roller bearing (01), Precision Ball Bearing (29), Ball Bearing (31)

Wheel Options

- **Note:** Select bearings featured are recommended for standard applications. For special applications or alternate bearings consult Acorn™.

NYLON/GLASS-FILLED/ NOISE REDUCTION - NR

Capacity Up to 1500 lbs.



Similar to NG wheels, but with the added benefit of two rubber treads on the wheel edges to reduce noise and improve traction even under heavy loads. Not recommended for towing applications above 3mph. Temperature range is -40° F to +180° F.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number*
4	2	800	2-3/16	1-3/16	1/2	1	NR0422908
5	2	1000	2-3/16	1-3/16	1/2	1	NR0522908
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	NR0622908
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	NR0822908

*Available with Stainless Steel Bearings (29SS).

*Roller bearing (01), Precision Ball Bearing (29), Ball Bearing (31)