

RETORT & FIBERGLASS FILLED POLYPROPYLENE

RETORT POLYPROPYLENE CALCIUM CORBONATE FILLED - RT

Capacity

Up to 900 lbs.



Designed to withstands the rigors of high temperature, these wheels are perfect for cooker racks and retort carts, clean rooms, bakeries and wet environments.

Dia. (inch)	Width (inch)	Capacity (Ibs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt (lbs)	Part Number
4	2	500	2-3/16	1-3/16	3/4	1	RT0420112
5	2	650	2-3/16	1-3/16	3/4	1/2	RT0520112
6	2	700	2-3/16	1-3/16	3/4	2	RT0620112
8	2	900	2-3/16	1-3/16	3/4	2-1/2	RT0820112

Delrin Bearing add 51 to the suffix

Roller Bearing & Roller Bearing stainless steel

*Available with dual Precision Ball Bearings & Stainless Steel Precision Ball Bearings

Features

• Wheel face: Moderate crown.

• Finish: White.

• Temperature Range: -20°F up to +290°F.

• Hardness: 75 Shore D

Same options as PB.

- Floor protective.
- Non-marking, non-chipping & non-absorbing.

FIBERGLASS FILLED POLYPROPYLENE - GP

Capacity

Up to 1400 lbs.



A new, innovative wheel featuring heavy-duty, reinforced fiberglass filled polypropylene.

Our test data shows that it last three times longer than the competition. Wheel has excellent mobility under heavy load and excellent chemical resistance.

Features

• Wheel face: Moderate crown.

• Finish: Black.

• Temperature Range: -20°F up to +250°F.

• Hardness: 65 Shore D.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt (lbs)	Part Number
4	2	800	2-3/16	1-3/16	3/4	1	GP0420112
4	2	800	2-3/16	1-3/16	1/2	1	GP0422908
4	2	800	2-3/16	1-3/16	1/2	1	GP0425108
5	2	1000	2-3/16	1-3/16	3/4	1	GP0520112
5	2	1000	2-3/16	1-3/16	1/2	1	GP0522908
5	2	1000	2-3/16	1-3/16	1/2	1	GP0525108
6	2	1200	2-3/16	1-3/16	3/4	1-1/8	GP0620112
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	GP0622908
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	GP0625108
8	2	1400	2-3/16	1-3/16	3/4	1-3/8	GP0820112
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	GP0822908
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	GP0825108