

# GHK-BB

## SERIES



Swivel Head Section



Total Lock System



Wheel Face Break



Directional Lock

### 1,500 Lbs. Load Capacity

### Forged Precision Bearing Maintenance Free Casters

Single piece Drop Forged AISI 1045 Steel Top Plate and Fork Base

Sealed Precision Ball Bearing Hydraulically Staked and sealed in the Swivel Head for life

Totally Sealed Swivel Head with Grease Nipple


1/4" Thick Fork Legs Robotically welded Inside & Outside to 2-1/2" fork spacing

1/2" Wheel axle

4 Position Directional Lock Slots


Finish : Bright Zinc Plated

#### Top Plate




4"x4-1/2"

#### Bolt Hole Centers



2-5/8" x 3-5/8"  
Slotted to  
3" x 3"

#### Attaching Bolt Size



3/8"

## 'GHK-BB' SERIES CASTERS WITH 'SAS' SERIES HIGH LOAD CAPACITY POLYURETHANE WHEELS

- High Load Capacity Liquid Cast Premium Polyurethane Wheels 93 ± 3 Shore A
- Polyurethane firmly bonded to precision machined Cast Iron Core
- Low rolling resistance, Smooth and Noiseless running.
- Non-Marking and floor protective.
- High Abrasion, Cut and Tear resistant
- 100% tested and guaranteed against Bond Failures.
- Bearing Options: Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings;
- Temperature Range: -40°F to + 180°F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-SAS	GHK-BB-42S-SAS-TL	GHK-BB-42R-SAS	4	2	900	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-SAS	GHK-BB-52S-SAS-TL	GHK-BB-52R-SAS	5	2	1200	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-SAS	GHK-BB-62S-SAS-TL	GHK-BB-62R-SAS	6	2	1500	7-1/2	4-9/16	6	10
GHK-BB-82S-SAS	GHK-BB-82S-SAS-TL	GHK-BB-82R-SAS	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-SAS	GHK-BB-102S-SAS-TL	GHK-BB-102R-SAS	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'ME' SERIES ERGONOMIC WHEELS

- Ergonomic Premium Polyurethane Wheels for low Push-Pull Efforts
- Polyurethane 93 ± 3 Shore A mechanically and chemically bonded to precision machined cores.
- Non-Marking and floor protective.
- 100% Tested and Guaranteed against bond failures
- Tread Options : Softer 80A – Yellow Tread (Specify ME-Z) and Harder 73D – Blue Tread (Specify ME-F)
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings;
- Temperature Range:- -40° F to + 180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-ME	GHK-BB-42S-ME-TL	GHK-BB-42R-ME	4	2	775	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-ME	GHK-BB-52S-ME-TL	GHK-BB-52R-ME	5	2	1000	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-ME	GHK-BB-62S-ME-TL	GHK-BB-62R-ME	6	2	1250	7-1/2	4-9/16	6	10
GHK-BB-82S-ME	GHK-BB-82S-ME-TL	GHK-BB-82R-ME	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-ME	GHK-BB-102S-ME-TL	GHK-BB-102R-ME	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'SZS' SERIES THICK TREADED ELASTIC URETHANE WHEELS

- Elastic 85±3 Shore A Liquid Cast Polyurethane firmly bonded to Cast Iron Core
- Reduced noise due to cushioning of loads,
- Lively' Polyurethane allows wheels to 'Flex and Roll' over debris
- Excellent for power towing applications
- Non-Marking and floor protective.
- 100% Tested and Guaranteed against bond failures
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings;
- Temperature Range:- -40° F to + 180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-SZS	GHK-BB-42S-SZS-TL	GHK-BB-42R-SZS	4	2	550	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-SZS	GHK-BB-52S-SZS-TL	GHK-BB-52R-SZS	5	2	775	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-SZS	GHK-BB-62S-SZS-TL	GHK-BB-62R-SZS	6	2	1000	7-1/2	4-9/16	6	10
GHK-BB-82S-SZS	GHK-BB-82S-SZS-TL	GHK-BB-82R-SZS	8	2	1450	9-1/2	6	6	11-1/2
GHK-BB-102S-SZS	GHK-BB-102S-SZS-TL	GHK-BB-102R-SZS	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'SFS' SERIES SOLID ELASTOMER WHEELS

- The Ultimate Real Solid Elastomer Wheels exclusively developed by Muvtons Premium Liquid Cast 73 ± 3 Shore D Polyurethane locked mechanically to a non-corrosive metallic core that holds the precision bearings and provides structural rigidity.
- Resist compression set and provide excellent resilience for easy movement
- Non-Marking and floor protective
- Can be used for corrosive applications with suitable bearings.
- 100% Tested and Guaranteed against failures
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range:- -40° F to + 180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-SFS	GHK-BB-42S-SFS-TL	GHK-BB-42R-SFS	4	2	850	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-SFS	GHK-BB-52S-SFS-TL	GHK-BB-52R-SFS	5	2	1100	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-SFS	GHK-BB-62S-SFS-TL	GHK-BB-62R-SFS	6	2	1500	7-1/2	4-9/16	6	10
GHK-BB-82S-SFS	GHK-BB-82S-SFS-TL	GHK-BB-82R-SFS	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-SFS	GHK-BB-102S-SFS-TL	GHK-BB-102R-SFS	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'SJS' SERIES POLYURETHANE WHEELS

- Liquid Cast Polyurethane 93 ± 3 Shore A firmly bonded to precision machined Cast Iron Cores.
- Low rolling resistance; Smooth and noiseless running
- Non-Marking and floor protective
- Good Abrasion and cut resistance
- 100% Tested and Guaranteed against bond failures
- Ideal for medium duty applications
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: -40° F to +180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-SJS	GHK-BB-42S-SJS -TL	GHK-BB-42R-SJS	4	2	700	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-SJS	GHK-BB-52S-SJS -TL	GHK-BB-52R-SJS	5	2	1000	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-SJS	GHK-BB-62S-SJS -TL	GHK-BB-62R-SJS	6	2	1200	7-1/2	4-9/16	6	10
GHK-BB-82S-SJS	GHK-BB-82S-SJS -TL	GHK-BB-82R-SJS	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-SJS	GHK-BB-102S-SJS -TL	GHK-BB-102R-SJS	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'SEB' SERIES HEAVY DUTY MOLDON RUBBER WHEELS

- Elastic Rubber tired wheels chemically bonded to precision machined Cast Iron Cores.
- Highly resilient 75 ± 5 Shore A rubber.
- Smooth and silent running in power towing applications.
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: -40° F to +180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-SEB	GHK-BB-42S-SEB-TL	GHK-BB-42R-SEB	4	2	460	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-SEB	GHK-BB-52S-SEB-TL	GHK-BB-52R-SEB	5	2	600	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-SEB	GHK-BB-62S-SEB-TL	GHK-BB-62R-SEB	6	2	775	7-1/2	4-9/16	6	10
GHK-BB-82S-SEB	GHK-BB-82S-SEB-TL	GHK-BB-82R-SEB	8	2	1000	9-1/2	6	6	11-1/2
GHK-BB-102S-SEB	GHK-BB-102S-SEB-TL	GHK-BB-102R-SEB	10	2	1100	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH MOR SERIES MOLDON RUBBER WHEELS

- Black rubber wheels firmly bonded to precision machined Cast Iron Cores
- Smooth and silent running
- Good quality 75 Shore A rubber with minimum Tensile Strength of 1000 psi
- Suitable for medium duty hand truck applications.
- Bearing Options:- Roller Bearings, Precision Ball Bearings;
- Temperature Range: -40° F to + 180° F



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-MOR	GHK-BB-42S-MOR-TL	GHK-BB-42R-MOR	4	2	350	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-MOR	GHK-BB-52S-MOR-TL	GHK-BB-52R-MOR	5	2	400	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-MOR	GHK-BB-62S-MOR-TL	GHK-BB-62R-MOR	6	2	450	7-1/2	4-9/16	6	10
GHK-BB-82S-MOR	GHK-BB-82S-MOR-TL	GHK-BB-82R-MOR	8	2	525	9-1/2	6	6	11-1/2
GHK-BB-102S-MOR	GHK-BB-102S-MOR-TL	GHK-BB-102R-MOR	10	2	700	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'MCI' SERIES CAST IRON WHEELS

- Special Grey cast iron wheels - solid core construction
- Fully machined tread faces – crown treaded for easy maneuverability.
- High abrasion and oil resistant
- Can be used upto 800° F with appropriate wheel bearings.
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: upto 800° F with appropriate bearings



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-MCI	GHK-BB-42S-MCI-TL	GHK-BB-42R-MCI	4	2	1000	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-MCI	GHK-BB-52S-MCI-TL	GHK-BB-52R-MCI	5	2	1200	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-MCI	GHK-BB-62S-MCI-TL	GHK-BB-62R-MCI	6	2	1500	7-1/2	4-9/16	6	10
GHK-BB-82S-MCI	GHK-BB-82S-MCI-TL	GHK-BB-82R-MCI	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-MCI	GHK-BB-102S-MCI-TL	GHK-BB-102R-MCI	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'MDW' SERIES DUCTILE STEEL WHEELS

- Special Ductile Cast Steel wheels with fully machined tread face
- Crown Tread Face makes maneuverability easy
- Higher Load Capacities compared to Cast Iron Wheels
- Suitable for extra heavy loads towed in punishing conditions.
- High abrasion and oil resistance
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: upto 800° F with appropriate bearings













Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
GHK-BB-42S-MDW	GHK-BB-42S-MDW-TL	GHK-BB-42R-MDW	4	2	1500	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-MDW	GHK-BB-52S-MDW-TL	GHK-BB-52R-MDW	5	2	1500	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-MDW	GHK-BB-62S-MDW-TL	GHK-BB-62R-MDW	6	2	1500	7-1/2	4-9/16	6	10
GHK-BB-82S-MDW	GHK-BB-82S-MDW-TL	GHK-BB-82R-MDW	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-MDW	GHK-BB-102S-MDW-TL	GHK-BB-102R-MDW	10	2	1500	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH 'DF' SERIES DROP FORGED STEEL WHEELS

- Hot forged from AISI 1045 steel with fully machined tread faces
- Virtually indestructible and easy to maneuver
- High abrasion and oil resistant
- Can be used in the roughest of applications on the poorest of floors
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: -150° F upto 800° F with appropriate bearings













Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
									
GHK-BB-42S-DF	GHK-BB-42S-DF-TL	GHK-BB-42R-DF	4	2	1800	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-DF	GHK-BB-52S-DF-TL	GHK-BB-52R-DF	5	2	2000	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-DF	GHK-BB-62S-DF-TL	GHK-BB-62R-DF	6	2	2000	7-1/2	4-9/16	6	10
GHK-BB-82S-DF	GHK-BB-82S-DF-TL	GHK-BB-82R-DF	8	2	2000	9-1/2	6	6	11-1/2
GHK-BB-102S-DF	GHK-BB-102S-DF-TL	GHK-BB-102R-DF	10	2	2000	11-1/2	7-1/2	7-1/2	13

## 'GHK-BB' SERIES CASTERS WITH MUVTUFF 'MCNY' SERIES CAST POLY WHEELS

- Machined from Tough, High Impact resistant Cast Polyamide
- Ultimate choice for Extremely High Load applications to replace metallic wheels
- Offer very high Abrasion resistance and very low rolling resistance under extreme loads
- Resistant to Salt, Grease, Alcohol and mild acids - can be used in corrosive applications with appropriate bearings
- Bearing Options:- Precision Ball Bearings; Tapered Roller Bearings  
Roller Bearings
- Temperature Range: -40° F to +180° F with appropriate bearings



Part No. Swivel Caster	Part No. Swivel with Total Lock	Part No. Rigid Caster	Wheel Dia (inch)	Tread Width (inch)	Load Capacity (Lbs)	Overall Height (inch)	Swivel Radius (inch)	Swivel Radius with Total Lock (inch)	Swivel Radius with Wheel Brake (inch)
									
GHK-BB-42S-MCNY	GHK-BB-42S-MCNY-TL	GHK-BB-42R-MCNY	4	2	1500	5-5/8	3-3/16	4	8-1/2
GHK-BB-52S-MCNY	GHK-BB-52S-MCNY-TL	GHK-BB-52R-MCNY	5	2	1500	6-1/2	3-7/8	4	9-1/2
GHK-BB-62S-MCNY	GHK-BB-62S-MCNY-TL	GHK-BB-62R-MCNY	6	2	1500	7-1/2	4-9/16	6	10
GHK-BB-82S-MCNY	GHK-BB-82S-MCNY-TL	GHK-BB-82R-MCNY	8	2	1500	9-1/2	6	6	11-1/2
GHK-BB-102S-MCNY	GHK-BB-102S-MCNY-TL	GHK-BB-102R-MCNY	10	2	1500	11-1/2	7-1/2	7-1/2	13