

VULKOLLAN® HEAVY-DUTY WHEELS

EURO (MM) DIMENSIONS



VUHD SERIES

VULKOLLAN® heavy-duty wheels

Stable welded wheel center with ball bearing (/5).
Direct bonded VULKOLLAN® tread (93° Shore A).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Fixing Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
VUHD/300/075/260/5/35	300	75	80	80	96	35	2.000
VUHD/300/100/260/5/35	300	100	110	110	116	35	2.500
VUHD/360/075/310/5/40	360	75	80	80	116	40	2.500
VUHD/360/100/310/5/40	360	100	110	110	116	40	3.000
VUHD/400/100/350/5/40	400	100	110	110	116	40	3.500
VUHD/400/120/350/5/50	400	120	130	130	116	50	4.000
VUHD/400/150/350/5/50	400	150	160	160	117	50	4.300
VUHD/500/100/450/5/50	500	100	110	110	136	50	4.500
VUHD/500/120/450/5/50	500	120	130	130	136	50	5.000
VUHD/500/150/450/5/50	500	150	160	160	136	50	5.700
VUHD/500/200/450/5/80	500	200	210	210	197	80	8.000
VUHD/600/150/550/5/80	600	150	160	160	203	80	8.000
VUHD/600/200/550/5/80	600	200	210	210	199	870	10.000

25.4 mm = 1 inch 1 kg = 2.2 lbs