



Total Lock Swivel Plate Caster
also available in Rigid and Swivel.

PLATE TYPE FEATURES

Thermoplastic Rubber Polypropylene Wheel Center on Polypropylene core. 90° Shore A: color gray, non-marking, smoothly rolling, 2RS precision ball bearing.

Mounted in a pressed stainless steel castor with double ball race: sealed, smooth rolling and pivoting - type: swivel, swivel + brake, fixed.

APPLICATIONS

- Temperature Range: -20°C to +60°C.
- Fully rust proof.
- Suitable for lighter applications, even on irregular to bad floors.
- Various applications in the construction of apparatus, furniture industry, and movement of shop equipment.

STAINLESS STEEL PLATE CASTER TPR WHEEL

25.4 mm = 1 inch

Swivel	Total Lock	Rigid	Wheel Diameter (mm)	Tread Width (mm)	Top Plate Size (mm)	Bolt Hole Spacing (mm)	Bolt Hole Diameter (mm)	Swivel Radius (mm)	Precision Ball Bearing (mm)	Overall Height (mm)	Load Capacity kg.
RT WK 050 IJU	RT WK 050 IJUS	RT WK 050 IVU	50	18	60x60	48x48	6	25	PB	69	40
RT WK 075 IJU	RT WK 075 IJUS	RT WK 075 IVU	75	25	60X60	48x48	8	24	PB	100	75



Total Lock Swivel Hole Caster

HOLE TYPE FEATURES

Thermoplastic Rubber Polypropylene Wheel Center on Polypropylene core. 90° Shore A: color gray, non-marking, smoothly rolling, 2RS precision ball bearing.

Mounted in a pressed stainless steel castor with double ball race: sealed, smooth rolling and pivoting - type: swivel, swivel + brake, fixed.

APPLICATIONS

- Temperature Range: -20°C to +60°C.
- Fully rust proof.
- Suitable for lighter applications, even on irregular to bad floors.
- Various applications in the construction of apparatus, furniture industry, and movement of shop equipment.

STAINLESS STEEL SWIVEL HOLE CASTER TPR WHEEL

25.4 mm = 1 inch

Swivel	Total Lock	Wheel Diameter (mm)	Tread Width (mm)	Swivel Radius (mm)	Top Plate Size (mm)	Hole Size (mm)	Precision Ball Bearing (mm)	Overall Height (mm)	Load Capacity kg.
RT WK 050 IJC	RT WK 050 IJCS	50	18	12	25	10	PB	69	40
RT WK 075 IJC	RT WK 075 IJCS	75	25	12	24	12	PB	100	75