

ELASTIC RUBBER ON NYLON - ERN

Capacity Up to 600 lbs.



Features

- 70-75 Durometer Shore A.
- Elastic rubber molded to nylon center.
- 6203 precision bearing.
- Easy rolling, impact resistant and shock absorption.
- 1/2" inner diameter top hat bushings available.
- Temperature -40°F up to +160°F.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Part Number
4	2	2-3/16	325	420ERN63U
5	2	2-3/16	475	520ERN63U
6	2	2-3/16	500	620ERN63U
8	2	2-3/16	600	820ERN63U

THERMOPLASTIC RUBBER - TPR & DPR

Capacity Up to 600 lbs.



Features

- Non-marking thermoplastic rubber tread on polyolefin core.
- 70 Durometer Shore A.
- Resist most solvents, oil, grease and water.
- Light weight, smooth rolling and quiet.
- Temperature -45°F up to +180°F.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Donut Tread Number	Part Number
4	2	2-3/16	450	420DPR38	420TPR38
5	2	2-3/16	500	520DPR38	520TPR38
6	2	2-3/16	550	620DPR38	620TPR38
8	2	2-3/16	600	820DPR38	820TPR38

Precision ball bearings 38 - 1/2" bore

HIGH TECH RUBBER - FX

Capacity Up to 315 lbs.



Features

- 65 Durometer Shore A.
- Economic option instead of Duratek PPR.
- Thermoplastic rubber bonded to polyolefin core.
- Non-marking.
- Great for factory, institutional and food service environments.
- Temperature -45°F up to +180°F.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Precision Ball Bearing	Part Number
3	1-1/4	1-1/2	225	35	314FX35
3-1/2	1-1/4	1-1/2	230	35	3514FX35
4	1-1/4	1-1/2	300	34, 35	414FX*
5	1-1/4	1-1/2	315	34, 35	514FX*

*Precision ball bearings 34, 35