

HI-TEMP/NYLON WHEELS HEATEATER - HE

Capacity Up to 1400 lbs.



Features

- **Wheel face:** Moderate crown.
- **Finish:** Black.
- **Temperature Range:** Up to 550°F, 475°F. intermittent consult Acorn™.
- **Hardness:** 85 Shore D ±5.
- For stainless steel roller bearing specify **ZB03**.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number P = Prec. Brg
4	2	800	2-3/16	1-3/16	3/4	1	HE0420112
5	2	1000	2-3/16	1-3/16	3/4	1-1/2	HE0520112
6	2	1200	2-3/16	1-3/16	3/4	1-1/2	HE0620112
8	2	1400	2-3/16	1-3/16	3/4	1-1/2	HE0820112

*Available with Stainless Steel Bearings (29SS).

Wheel Options

Note:

Select bearings featured are recommended for standard applications.

For special applications or alternate bearings, please consult Acorn™.

For customization & special application options, please consult Acorn™.

Ideal for speciality applications, these wheels can withstand intermittent temperatures up to 550° F. Nylon Glass-filled wheels won't chip, absorb water or breakdown in caustic environments.

NYLON WHITE WHEELS NW

Capacity Up to 1100 lbs.



Features

- **Wheel face:** Moderate crown.
- Composed of injection molded white nylon
- Maximum performance, economical solution for your most demanding caster applications.
- Excellent ergonomics. Wheel starts rolling, keeps rolling and swivels with ease!
- **Temperature Range:** -20°F to 250°F .
- **Hardness:** 85 Shore D ±5.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Bearing	Part Number
5	2	600	2-3/16	1-3/16	1/2	1	Ped. Prec. Ball	NW0522908
6	2	900	2-3/16	1-3/16	1/2	1-1/4	Ped. Prec. Ball	NW0622908
8	2	1100	2-3/16	1-3/16	1/2	2	Ped. Prec. Ball	NW0822908

*Available with Stainless Steel Bearings (29SS).

Wheel Options

Note:

Select bearings featured are recommended for standard applications.

For special applications or alternate bearings please consult Acorn™.

For customization & special application options, please consult Acorn™.