

NEVER FLAT TIRES - NF

Capacity Up to 350 lbs.



Looks and performs similar to pneumatic wheels, but without the hassles of air pressure maintenance and flat tire repair. Also reduces maintenance time and expense. Closed cell expanded foam construction resists water absorption (unlike others currently in the marketplace).

Features

- Radial sawtooth tread for easy maneuverability and traction (radial tread on 8" model).
- Quiet, smooth operation.
- Non-marking for superior floor protection.
- Rolls over obstacles with ease and absorbs shock to protect cargo.

Dia. (inch)	Width (inch)	Capacity (lbs.)	Hub Description	Bearing ID (inch)	Wt. (lbs.)	Part Number
8	3	300	Offset 1-Piece Hub	1/2	4	NF0852708
8	3	300	Offset 1-Piece Hub	5/8	4	NF0852710
8	3	300	Centered 1-Piece Hub	1/2	4	NF0852708C
8	3	300	Offset 3-Piece Hub	1/2	4	NF0852708T
8	3	300	Offset 3-Piece Hub	5/8	4	NF0852710T
8	3	300	Centered 3-Piece Hub	1/2	4	NF0852708CT
8	3	300	Centered 3-Piece Hub	5/8	4	NF0852710CT

Ball Bearing (27)

Looks and performs similar to pneumatic wheels, but without the hassles of air pressure maintenance and flat tire repair. Also reduces maintenance time and expense. Closed cell expanded foam construction resists water absorption (unlike others currently in the marketplace)

MONOPRENE PNEUMATIC - SZ/SV

Capacity Up to 280 lbs.



The SZ (black) and SV (gray) wheels provide you with all the benefits of a pneumatic tire, without the hassle of getting a flat. These maintenance-free wheels, constructed of solid

monoprene material, which rejects debris and will not go flat, offer the same great features of a pneumatic wheel.

Dia. (inch)	Width (inch)	Capacity (lbs.)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Part Number
SZ Monoprene Pneumatic						
6	2	250	2-7/16	1-3/16	1/2	SZ0622708
8	2	280	2-7/16	1-3/16	3/4	SZ0622712
SV Monoprene Pneumatic						
6	2	250	2-7/16	1-3/16	1/2	SV0622708
8	2	280	2-7/16	1-3/16	3/4	SV0622712