

RETORT & FIBERGLASS FILLED POLYPROPYLENE

RETORT POLYPROPYLENE CALCIUM CARBONATE FILLED - RT

Capacity Up to 900 lbs.



Designed to withstand the rigors of high temperature, these wheels are perfect for cooker racks and retort carts, clean rooms, bakeries and wet environments.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt (lbs)	Part Number
4	2	500	2-3/16	1-3/16	3/4	1	RT0420112
5	2	650	2-3/16	1-3/16	3/4	1/2	RT0520112
6	2	700	2-3/16	1-3/16	3/4	2	RT0620112
8	2	900	2-3/16	1-3/16	3/4	2-1/2	RT0820112

Delrin Bearing add 51 to the suffix

Roller Bearing & Roller Bearing stainless steel

*Available with dual Precision Ball Bearings & Stainless Steel Precision Ball Bearings


Features

- **Wheel face:** Moderate crown.
- **Finish:** White.
- **Temperature Range:** -20°F up to +290°F.
- **Hardness:** 75 Shore D
- Floor protective.
- Non-marking, non-chipping & non-absorbing.

Same options as PB.

FIBERGLASS FILLED POLYPROPYLENE - GP

Capacity Up to 1400 lbs.



A new, innovative wheel featuring heavy-duty, reinforced fiberglass filled polypropylene. Our test data shows that it lasts three times longer than the competition. Wheel has excellent mobility under heavy load and excellent chemical resistance.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt (lbs)	Part Number
4	2	800	2-3/16	1-3/16	3/4	1	GP0420112
4	2	800	2-3/16	1-3/16	1/2	1	GP0422908
4	2	800	2-3/16	1-3/16	1/2	1	GP0425108
5	2	1000	2-3/16	1-3/16	3/4	1	GP0520112
5	2	1000	2-3/16	1-3/16	1/2	1	GP0522908
5	2	1000	2-3/16	1-3/16	1/2	1	GP0525108
6	2	1200	2-3/16	1-3/16	3/4	1-1/8	GP0620112
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	GP0622908
6	2	1200	2-3/16	1-3/16	1/2	1-1/8	GP0625108
8	2	1400	2-3/16	1-3/16	3/4	1-3/8	GP0820112
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	GP0822908
8	2	1400	2-3/16	1-3/16	1/2	1-3/8	GP0825108

Features

- **Wheel face:** Moderate crown.
- **Finish:** Black.
- **Temperature Range:** -20°F up to +250°F.
- **Hardness:** 65 Shore D.