

POLYURETHANE ON NYLON CORE

ELECTRICALLY CONDUCTIVE WHEELS

EURO (MM) DIMENSIONS



SERIES UNC

SERIES UNC/HD

Electrically conductive wheels

Electrically conductive rim with a tread made of high-quality thermoplastic polyurethane (96° Shore A), with ball bearings (/5) or stainless ball bearings (/5R).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Fixing Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
UNC/080/035/5/12	80	35	31	31	41	12	110
UNC/100/040/5/15	100	40	45	41	45	15	160
UNC/125/045/5/15	125	45	45	41	45	15	250
UNC/150/050/5/20	150	50	55	58	65	20	280
UNC/160/050/5/20	160	50	55	51	65	20	300
UNC/200/050/5/20	200	50	55	51	60	20	400
UNC/080/035/5R/12	80	35	31	31	41	12	11
UNC/100/040/5R/15	100	40	45	41	45	15	160
UNC/125/045/5R/15	125	45	45	41	45	15	250
UNC/150/050/5R/20	150	50	55	58	65	20	280
UNC/160/050/5R/20	160	50	55	51	65	20	300
UNC/200/050/5R/20	200	50	55	51	60	20	400

25.4 mm = 1 inch 1 kg = 2.2 lbs

All wheels can fit in US caster rigs.

Electrically conductive wheels with ball bearings

High-quality thermoplastic polyamid. Wheels in heavy-duty design with ball bearings (/5) or stainless ball bearings (/5R).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Fixing Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
UNC/HD/080/035/5/12	80	35	35	33	50	12	300
UNC/HD/100/040/5/15	100	40	45	41	48	15	450
UNC/HD/125/045/5/15	125	40	53	53	60	20	600
UNC/HD/150/050/5/20	150	50	55	53	65	20	600
UNC/HD/200/050/5/20	200	50	55	53	65	20	1.000
UNC/HD/080/035/5R/12	80	35	35	33	50	12	300
UNC/HD/100/040/5R/15	100	40	45	41	48	15	450
UNC/HD/125/045/5R/15	125	40	53	53	60	20	600
UNC/HD/150/050/5R/20	150	50	55	53	65	20	600
UNC/HD/200/050/5R/20	200	50	55	53	65	20	1.000

25.4 mm = 1 inch 1 kg = 2.2 lbs

All wheels can fit in US caster rigs.