

VULKOLLAN® PALLET ROLLERS

EURO (MM) DIMENSIONS




VUPR SERIES

VULKOLLAN® pallet rollers with ball bearings

Roller body made of steel tube with ball bearings. Direct bonded VULKOLLAN® tread (93° Shore A).

Item #	Wheel Diameter (mm)	Roller Width (mm)	Fitting Length (mm)	Bore Diameter (mm)	Load Capacity (kg)
VUPR/80/054/060/20	80	54	60	20	400
VUPR/80/057/059/20	80	57	59	20	400
VUPR/80/057/061/20	80	57	61	20	400
VUPR/80/057/061/25	80	57	61	25	400
VUPR/80/070/074/20	80	70	74	20	450
VUPR/80/100/104/20	80	100	104	20	600
VUPR/82/034/034,6/17	82	34	34,6	17	250
VUPR/82/050/052/20	82	50	52	20	400
VUPR/82/053/055/17*	82	53	55	17	400
VUPR/82/065/063/20	82	65	63	17	450
VUPR/82/065/067/20	82	65	67	17	450
VUPR/82/069/062/20	82	69	62	17	500
VUPR/82/070/066/20	82	70	66	17	500
VUPR/82/070/072/20	82	70	72	17	500
VUPR/82/070/074/20	82	70	74	17	500
VUPR/82/072/078/20	82	72	78	17	500
VUPR/82/072/078/20*	82	72	78	17	500
VUPR/82/082/086/20	82	82	86	17	600
VUPR/82/089/082/20	82	89	82	17	650
VUPR/82/098/105/20	82	98	105	17	700
VUPR/82/098/105/20*	82	98	105	17	700
VUPR/82/100/095/20	82	100	95	17	700
VUPR/82/100/104/20	82	100	104	17	700
VUPR/85/043/043/20	85	43	43	20	300
VUPR/85/046/048/25	85	46	48	25	350
VUPR/85/046/050/20	85	46	50	20	350
VUPR/85/050/055/25*	85	50	55	25	400
VUPR/85/055/060/20*	85	55	60	20	420
VUPR/85/059,5/061,5/17*	85	59,5	61,5	17	450

25.4 mm = 1 inch 1 kg = 2.2 lbs



V-ring sealing gasket

VULKOLLAN® PALLET ROLLERS

EURO (MM) DIMENSIONS




VUPR SERIES


Item #	Wheel Diameter (mm)	Roller Width (mm)	Fitting Length (mm)	Bore Diameter (mm)	Load Capacity (kg)
VUPR/85/061/065/20	85	61	65	20	450
VUPR/85/070/063/17	85	70	63	17	500
VUPR/85/075/077/20	85	75	77	20	550
VUPR/85/075/080/20*	85	75	80	20	580
VUPR/85/078/078/20	85	78	78	20	600
VUPR/85/078/080/20	85	78	80	20	600
VUPR/85/080/082/17*	85	80	82	17	600
VUPR/85/080/082/25	85	80	82	25	600
VUPR/85/080/084/20*	85	80	84	20	600
VUPR/85/080/085/20*	85	80	85	20	600
VUPR/85/086,5/088,5/17*	85	86,5	88,5	17	650
VUPR/85/090/092/25	85	90	92	25	700
VUPR/85/095/100/20*	85	95	100	20	750
VUPR/85/100/102/17*	85	100	102	17	800
VUPR/85/100/102/25*	85	100	102	25	800
VUPR/85/100/104/25	85	100	104	25	800
VUPR/85/105/110/25*	85	105	110	25	800
VUPR/85/120/124/20	85	120	124	20	900

* with labyrinth sealing


25.4 mm = 1 inch 1 kg = 2.2 lbs



ZZV-ball bearing



Labyrinth sealing



V-ring sealing gasket

VULKOLLAN® PALLET ROLLERS

EURO (MM) DIMENSIONS




VKS SERIES

Item #	Wheel Diameter (mm)	Roller Width (mm)	Fitting Length (mm)	Bore Diameter (mm)	Load Capacity (kg)
VKS/80/074/076/13	80	74	76	13	500
VKS/80/095/100/20	80	74	76	13	500
VKS/82/050/055/20	82	50	55	20	350
VKS/82/065/070/20	82	65	70	20	450
VKS/82/069/074/20	82	69	74	20	500
VKS/82/070/075/20	82	70	75	20	500
VKS/82/072/077/17	82	72	77	17	500
VKS/82/075/080/20	82	75	80	20	550
VKS/85/060/065/12	85	60	65	12	450
VKS/85/060/065/20	85	60	65	20	450
VKS/85/060/065/25	85	60	65	25	450
VKS/85/070/075/20	85	70	75	20	500
VKS/85/070/075/25	85	70	75	25	500
VKS/85/073/078/20	85	73	78	20	550
VKS/85/075/080/12	85	75	80	12	580
VKS/85/075/080/20	85	75	80	20	550
VKS/85/075/080/25	85	75	80	25	550
VKS/85/078/082/12	85	78	82	12	600
VKS/85/080/082/17	85	80	82	17	600
VKS/85/080/085/12	85	80	85	12	600
VKS/85/080/085/20	85	80	85	20	600
VKS/85/080/085/25	85	80	85	25	490
VKS/85/085/089,7/25	85	85	89,7	25	660
VKS/85/085/090/12	85	85	90	12	650
VKS/85/085/090/20	85	85	90	20	650
VKS/85/085/090/25	85	85	90	25	650
VKS/85/090/095/20	85	90	95	20	700
VKS/85/090/095/25	85	90	95	25	700
VKS/85/095/100/17	85	95	100	17	750
VKS/85/095/100/20	85	95	100	20	750
VKS/85/095/100/25	85	95	100	25	750
VKS/85/100/105/20	85	100	105	20	800
VKS/85/100/105/25	85	100	105	25	800
VKS/85/105/110/13	85	105	110	13	800
VKS/85/105/110/20	85	105	110	20	800
VKS/85/105/110/25	85	105	110	25	800
VKS/85/110/115/25	85	100	115	25	850

25.4 mm = 1 inch 1 kg = 2.2 lbs

VULKOLLAN® pallet rollers with sealed ball bearings

Roller body made of steel tube with ball bearings. Direct bonded VULKOLLAN® tread (93° Shore A). Plastic sealing and V-ring gasket for protection of the ball bearing against splash water and foreign matter.



V-ring sealing gasket