

POLYPROPYLENE BLACK - PB

Capacity Up to 1000 lbs.



Injection molded blend of thermoplastic polymers which resist absorption and are resistant to most chemicals and solvents. Capacity ratings are comparable to hard rubber wheels with the added advantage of being lighter in weight and having greater impact resistance.

Features

- **Wheel face:** Moderate crown.
- **Finish:** Black.
- **Temperature Range:** -20°F to +180°F.
- **Hardness:** 65 Shore D.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number
4	2	450	2-3/16	1-3/16	3/4	1	PB0420112
5	2	650	2-3/16	1-3/16	3/4	1-1/4	PB0520112
6	2	750	2-3/16	1-3/16	3/4	1-1/2	PB0624112
8	2	1000	2-3/16	1-3/16	3/4	1-3/4	PB0820112

Delrin Bearing add 51 to the suffix

Available with Standard Ball Bearing & Stainless Steel Ball Bearing

^ = Wheels are complete with spanner bushing & nylon retaining thrust washers
< = 2-7/16" Spanner and Spacers included

POLYPROPYLENE WHITE - PW

Capacity Up to 750 lbs.



Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number
4	2	450	2-3/16	3/4	3/4	3/4	PW0424112
4	2	450	2-3/16	1/2	1/2	3/4	PW0424108
5	2	550	2-3/16	3/4	3/4	3/4	PW0524112
5	2	650	2-3/16	1/2	1/2	3/4	PW0524108
5	2	650	2-3/8	1/2	3/4	3/4	PW0525112
6	2	650	2-3/16	3/4	3/4	3/4	PW0624112
6	2	750	2-3/16	1/2	1/2	3/4	PW0624108
6	2	750	2-3/8	1/2	3/4	3/4	PW0625111

Delrin Bearing add 51 to the suffix

Available with Standard Ball Bearing & Stainless Steel Ball Bearing

^ = Wheels are complete with spanner bushing & nylon retaining thrust washers
< = 2-7/16" Spanner and Spacers included