

1

1N LIGHT DUTY LOW PROFILE Polyurethane with Precision Ball Bearing



Plate Swivel Caster




PLATE TYPE FEATURES

Load Capacity Up to 220 lbs. (100 kg.)

Casters: Pressed steel, swivel bracket with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.

Wheels: Polyurethane, firmly bonded, color light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance. Very good chemical connection with the wheel center.

Made of steel **with precision ball bearings.**

SWIVEL CASTER WITH POLYURETHANE WHEELS

25.4 mm = 1 inch

Wheel Dia. (mm)	Wheel Width (mm)	Capacity (lb)	Bearing Type	OAH (mm)	Plate (mm)	Bolt Hole Spacing (mm)	Bolt Hole (mm)	Offset (mm)	Swivel Part Number
35	27	220	Precision Ball	52	60 x 60	38 x 38 / 48 x 48	6, 5	15	1NWR0350GR0
45	27	220	Precision Ball	62	60 x 60	38 x 38 / 48 x 48	6, 5	15	1NWK0450GR0
55	27	220	Precision Ball	72	60 x 60	38 x 38 / 48 x 48	6, 5	15	1NWK0550GR0



Hole Swivel Caster

HOLE TYPE FEATURES

Load Capacity Up to 220 lbs. (100 kg.)

Casters: Pressed steel, swivel bracket with double ball bearing in the swivel head, bolted wheel axle, zinc-plated.

Wheels: Made of polyurethane, firmly bonded, color light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance. Very good chemical connection with the wheel center.

Made of steel **with precision ball bearings.**

HOLE CASTER WITH POLYURETHANE WHEELS

25.4 mm = 1 inch

Wheel Dia. (mm)	Wheel Width (mm)	Capacity (lb)	Bearing Type	OAH (mm)	Plate (mm)	Bolt Hole (mm)	Offset (mm)	Swivel Part Number
35	27	220	Precision Ball	52	43	11	15	1NWR0350QR0
45	27	220	Precision Ball	62	43	11	15	1NWK0450QR0
55	27	220	Precision Ball	72	43	11	15	1NWK0550QR0

Nylacron wheels are available with precision ball bearings for all sizes.

Stems available on request.