

Total Lock Swivel Plate Caster
also available in Rigid and Swivel.

PLATE TYPE FEATURES

Thermoplastic Rubber Polypropylene Wheel Center on Polypropylene core. 90° Shore A: color gray, non-marking, smoothly rolling, 2RS precision ball bearing.

Mounted in a pressed stainless steel castor with double ball race: sealed, smooth rolling and pivoting - type: swivel, swivel + brake, fixed.


APPLICATIONS

- Temperature Range: -20°C to +60°C.
- Fully rust proof.
- Suitable for lighter applications, even on irregular to bad floors.
- Various applications in the construction of apparatus, furniture industry, and movement of shop equipment.

STAINLESS STEEL PLATE CASTER TPR WHEEL

25.4 mm = 1 inch

| Swivel | Total Lock | Rigid | Wheel Diameter (mm) | Tread Width (mm) | Top Plate Size (mm) | Bolt Hole Spacing (mm) | Bolt Hole Diameter (mm) | Swivel Radius (mm) | Precision Ball Bearing (mm) | Overall Height (mm) | Load Capacity kg. |
|---------------|----------------|---------------|---------------------|------------------|---------------------|------------------------|-------------------------|--------------------|-----------------------------|---------------------|-------------------|
| VT WK 050 IJU | VT WK 050 IJUS | VT WK 050 IVU | 50 | 18 | 60x60 | 48x48 | 6 | 25 | PB | 69 | 40 |
| VT WK 075 IJU | VT WK 075 IJUS | VT WK 075 IVU | 75 | 25 | 60X60 | 48x48 | 8 | 24 | PB | 100 | 75 |



Total Lock Swivel Hole Caster

HOLE TYPE FEATURES

Thermoplastic Rubber Polypropylene Wheel Center on Polypropylene core. 90° Shore A: color gray, non-marking, smoothly rolling, 2RS precision ball bearing.

Mounted in a pressed stainless steel castor with double ball race: sealed, smooth rolling and pivoting - type: swivel, swivel + brake, fixed.

APPLICATIONS

- Temperature Range: -20°C to +60°C.
- Fully rust proof.
- Suitable for lighter applications, even on irregular to bad floors.
- Various applications in the construction of apparatus, furniture industry, and movement of shop equipment.

STAINLESS STEEL SWIVEL HOLE CASTER TPR WHEEL

25.4 mm = 1 inch

| Swivel | Total Lock | Wheel Diameter (mm) | Tread Width (mm) | Swivel Radius (mm) | Top Plate Size (mm) | Hole Size (mm) | Precision Ball Bearing (mm) | Overall Height (mm) | Load Capacity kg. |
|---------------|----------------|---------------------|------------------|--------------------|---------------------|----------------|-----------------------------|---------------------|-------------------|
| VT WK 050 IJC | VT WK 050 IJCS | 50 | 18 | 12 | 25 | 10 | PB | 69 | 40 |
| VT WK 075 IJC | VT WK 075 IJCS | 75 | 25 | 12 | 24 | 12 | PB | 100 | 75 |