

# MOLD-ON RUBBER ON DIE CAST ALUMINUM

## MOLD-ON RUBBER/ ALUMINUM CORE - MD

**Capacity**      **Up to 600 lbs.**



Cushion rubber treads are vulcanized to die cast aluminum core. The soft rubber tread affords a cushion effect to the load and excellent floor protection. These wheels are highly shock absorbing and provide quiet operation, while dampening vibration.

### Features

- **Wheel face:** Moderate crown.
- **Finish:** Blue on natural aluminum core.  
Red or Black or other treads available.
- **Temperature Range:** -40°F up to +180°F.
- **Hardness:** 80-83 Shore A.

### Wheel Options

- **Note:** Select bearings featured are recommended for standard applications. For special applications or alternate bearings consult Acorn™.
- For customization & special application options, please consult Acorn™.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number*
4	2	400	2-3/16	1-3/16	1/2	1-1/2	MD0420108
4	2	400	2-3/16	1-3/16	5/8	1-1/2	MD0420110
4	2	400	2-3/16	1-3/16	3/4	1-1/2	MD0420112
5	2	500	2-3/16	1-3/16	1/2	2	MD0520108
5	2	500	2-3/16	1-3/16	5/8	2	MD0520110
5	2	500	2-3/16	1-3/16	3/4	2	MD0520112
6	2	550	2-3/16	1-3/16	1/2	2-1/4	MD0620108
6	2	550	2-3/16	1-3/16	5/8	2-1/4	MD0620110
6	2	550	2-3/16	1-3/16	3/4	2-1/4	MD0420112
8	2	600	2-3/16	1-3/16	1/2	3-1/2	MD0820108
8	2	600	2-3/16	1-3/16	5/8	3-1/2	MD0820110
8	2	600	2-3/16	1-3/16	3/4	3-1/2	MD0820112

### Roller Bearing (01)

^ = Wheels are complete with spanner bushing & nylon retaining thrust washers

< = 2-7/16" Spanner and Spacers included