

3,000 LBS. LOAD CAPACITY STAINLESS STEEL KINGPINLESS TYPE CASTERS

- **Top Plate:** 5/16" 304 stainless steel welded inside and out to 316 stainless steel raceway for longer life.
- **Swivel Section:** One row of 1/2" ball bearings mounted in a precision machined raceway. Zerk in swivel section.
- **Yoke Base:** Notched 316 stainless steel.
- **Legs:** 304 stainless steel welded inside and outs.
- **Axle:** 3/4" diameter.
- Alternate or custom caster configurations available.

BRAKES OPTIONS



Poly Cam
specify P




Single Sided specify **SSB310**
Double Sided specify **DSB310**



Face Contact
specify **FBB**



Hand Operated Swivel Lock
specify **SL3000000**



TOE GUARDS AVAILABLE WITH ALL CASTERS.

Designed from premium grade 304 stainless steel caster rig with a strong premium 316 stainless swivel section. Excellent finish to protect caster from cleaning agents, steam, caustic solutions, or other corrosive agents which can cause rust.

TYPICAL APPLICATIONS

- Conveyor-drawn tow-trucks
- Heavy duty bakery racks
- Production dollies
- Heavy duty dough troughs

MOUNTING PLATE OPTIONS

TOP PLATE: (STANDARD)

Plate Size: 4-1/2 X 6-1/4
Bolt Holes: 2-7/16 x 4-15/16
slotted to
3-3/8 x 5-1/4
Bolt Size: 1/2

TOP PLATE: D

Plate Size: 5 x 5-1/2
Bolt Holes: 4-1/8 x 4-1/2
Bolt Size: 3/8

BEARING OPTIONS


Straight Roller **(01)**
Precision Ball **(28)**

*Add options to end of part number.

**NYLACRON™
CAST NYLON
28 PRECISION BEARING
NY/MD**

FOR MONOCAST
MC/MD

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
330SS63NYMD	330SR63NYMD	6	3	3000	7-1/2	1-3/8
330SS83NYMD	330SR83NYMD	8	3	3000	10-1/8	2-1/16
330SS103NYMD	330SR103NYMD	10	3	3000	11-1/2	2-1/4
330SS123NYMD	330SR123NYMD	12	3	3000	13-1/2	2-11/16



**X-TREME
PLUS SOLID POLYURETHANE
28 PRECISION BEARING
XP**

• Prevenz™ antimicrobial models available

• Add PREV to end of caster number

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
330SS83XP	330SR83XP	8	3	2000	10-1/8	2-1/16
330SS103XP	330SR103XP	10	3	2500	11-1/2	2-1/4



**PHENOLIC
01 ROLLER BEARING
TM**

• Prevenz™ antimicrobial models available

• Tapered Roller 09 Bearings available

• Add PREV to end of caster number

• Change "01" to "09"
Example: 6KSSS63TM09

Part Number Swivel Caster	Part Number Rigid Caster	Wheel Diameter (inch)	Tread Width (inch)	Load Capacity (lbs)	Overall Height (inch)	Swivel Lead (inch)
330SS63TM	330SR63TM	6	3	2000	7-1/2	1-3/8
330SS83TM	330SR83TM	8	3	2500	10-1/8	2-1/16
330SS103TM	330SR103TM	10	3	2900	11-1/2	2-1/4
330SS123TM	330SR123TM	12	3	3000	13-1/2	2-11/16



MEGALOAD™ AND VULKOLLAN™ WHEELS WITH PRECISION BALL BEARINGS AVAILABLE TO FIT THIS CASTER SERIES.

SIZES 6 X 3, 8 X 3, 10 X 3 & 12 X 3.