



3,000 LBS. LOAD CAPACITY STAINLESS STEEL KINGPINLESS TYPE CASTERS

- **Top Plate:** 5/16" 304 stainless steel welded inside and out to 316 stainless steel raceway for longer life.
- **Swivel Section:** One row of 1/2" ball bearings mounted in a precision machined raceway. Zerk in swivel section.
- **Yoke Base:** Notched 316 stainless steel.
- **Legs:** 304 stainless steel welded inside and outs.
- **Axle:** 3/4" diameter.
- Alternate or custom caster configurations available.

BRAKES OPTIONS



Poly Cam
specify **P**



Single Sided specify **SSB310**
Double Sided specify **DSB310**



Face Contact
specify **FBB**



Hand Operated Swivel Lock
specify **SL3000000**



TOE GUARDS AVAILABLE WITH ALL CASTERS.

Designed from premium grade 304 stainless steel caster rig with a strong premium 316 stainless swivel section. Excellent finish to protect caster from cleaning agents, steam, caustic solutions, or other corrosive agents which can cause rust.

TYPICAL APPLICATIONS

- Conveyor-drawn tow-trucks
- Heavy duty bakery racks
- Production dollies
- Heavy duty dough troughs

MOUNTING PLATE OPTIONS

TOP PLATE: (STANDARD)

Plate Size: 4-1/2 X 6-1/4
Bolt Holes: 2-7/16 x 4-15/16
slotted to
3-3/8 x 5-1/4
Bolt Size: 1/2

TOP PLATE: D

Plate Size: 5 x 5-1/2
Bolt Holes: 4-1/8 x 4-1/2
Bolt Size: 3/8

BEARING OPTIONS

Straight Roller **(01)**
Precision Ball **(28)**

*Add options to end of part number.

**NYLACRON™
CAST NYLON
28 PRECISION BEARING
NY/MD**

FOR MONOCAST
MC/MD

| Part Number Swivel Caster | Part Number Rigid Caster | Wheel Diameter (inch) | Tread Width (inch) | Load Capacity (lbs) | Overall Height (inch) | Swivel Lead (inch) |
|---------------------------------|--------------------------------|-----------------------------|--------------------------|---------------------------|-----------------------------|--------------------------|
| 330SS63NYMD | 330SR63NYMD | 6 | 3 | 3000 | 7-1/2 | 1-3/8 |
| 330SS83NYMD | 330SR83NYMD | 8 | 3 | 3000 | 10-1/8 | 2-1/16 |
| 330SS103NYMD | 330SR103NYMD | 10 | 3 | 3000 | 11-1/2 | 2-1/4 |
| 330SS123NYMD | 330SR123NYMD | 12 | 3 | 3000 | 13-1/2 | 2-11/16 |



**X-TREME
PLUS SOLID POLYURETHANE
28 PRECISION BEARING
XP**

• Prevenz™ antimicrobial models available

• Add PREV to end of caster number

| Part Number Swivel Caster | Part Number Rigid Caster | Wheel Diameter (inch) | Tread Width (inch) | Load Capacity (lbs) | Overall Height (inch) | Swivel Lead (inch) |
|---------------------------------|--------------------------------|-----------------------------|--------------------------|---------------------------|-----------------------------|--------------------------|
| 330SS83XP | 330SR83XP | 8 | 3 | 2000 | 10-1/8 | 2-1/16 |
| 330SS103XP | 330SR103XP | 10 | 3 | 2500 | 11-1/2 | 2-1/4 |



**PHENOLIC
01 ROLLER BEARING
TM**

• Prevenz™ antimicrobial models available

• Tapered Roller 09 Bearings available

• Add PREV to end of caster number

• Change "01" to "09"
Example: 6KSSS63TM09

| Part Number Swivel Caster | Part Number Rigid Caster | Wheel Diameter (inch) | Tread Width (inch) | Load Capacity (lbs) | Overall Height (inch) | Swivel Lead (inch) |
|---------------------------------|--------------------------------|-----------------------------|--------------------------|---------------------------|-----------------------------|--------------------------|
| 330SS63TM | 330SR63TM | 6 | 3 | 2000 | 7-1/2 | 1-3/8 |
| 330SS83TM | 330SR83TM | 8 | 3 | 2500 | 10-1/8 | 2-1/16 |
| 330SS103TM | 330SR103TM | 10 | 3 | 2900 | 11-1/2 | 2-1/4 |
| 330SS123TM | 330SR123TM | 12 | 3 | 3000 | 13-1/2 | 2-11/16 |



MEGALOAD™ AND VULKOLLAN™ WHEELS WITH PRECISION BALL BEARINGS AVAILABLE TO FIT THIS CASTER SERIES.
SIZES 6 X 3, 8 X 3, 10 X 3 & 12 X 3.