

300 LBS. LOAD CAPACITY CASTERS

- · Double ball bearing swivel raceway
- · Zinc plated standard
- Top plate and yoke 1/4"cold forged steel
- 5/8" riveted kingpin
- 1/2" diameter axle and lock nut
- · Shock absorbing
- · Grease fittings in swivel raceway
- · Quiet rolling and easy moving
- · Pneumatic flat free wheels

RIG OPTIONS

CS Swivel CR Rigid

TS Swivel/Top Lock Brake
DSB Double Side Brake
SL Swivel Lock

BRAKES OPTIONS

Single Side and **Double Sided** Brakes available. Consult Factory.

Swivel Lock available (welded) Consult Factory.

The 100 Series casters provides a smooth and easy movement. The grease fittings and 4-ply rubber pneumatics make the 100 Series perfect for carts, platform trucks, and more.

TYPICAL APPLICATIONS

- Platform Trucks
- Institutional
- Commercial
- · Lawn and Garden

MOUNTING

TOP PLATE: (STANDARD)

Plate Size: 4" x 4-1/2" Bolt Holes: 2-5/8" x 3-5/8" slotted to 3" x 3"

Bolt Size: 3/8"

Part Numbe Swivel Caster	r Part Number Rigid Caster	Part Number Top Lock	Wheel Diameter (inch)	Tread Width (inch)	Wheel Type	Load Capacity (inch)	Overall Height (inch)	Radius (inch)
100CS620FF4	503 100CR620FF4503	100TS620FF4503	6	2	Flat-Free	250	7-1/2	4-1/2
100CS830FF4	503 100CR830FF4503	100TS830FF4503	8	3	Flat-Free	300	9-3/4	6-1/2