

VULKOLLAN® HEAVY-DUTY WHEELS

EURO (MM) DIMENSIONS



VUHD SERIES

VULKOLLAN® heavy-duty wheels

Stable welded wheel center
with ball bearing (/5).
Direct bonded VULKOLLAN®
tread (93° Shore A).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Fixing Length (mm)	Hub Diameter (mm)	Bearing ID (mm)	Load Capacity (kg)
VUHD/300/075/260/5/35	300	75	80	80	96	35	2.000
VUHD/300/100/260/5/35	300	100	110	110	116	35	2.500
VUHD/360/075/310/5/40	360	75	80	80	116	40	2.500
VUHD/360/100/310/5/40	360	100	110	110	116	40	3.000
VUHD/400/100/350/5/40	400	100	110	110	116	40	3.500
VUHD/400/120/350/5/50	400	120	130	130	116	50	4.000
VUHD/400/150/350/5/50	400	150	160	160	117	50	4.300
VUHD/500/100/450/5/50	500	100	110	110	136	50	4.500
VUHD/500/120/450/5/50	500	120	130	130	136	50	5.000
VUHD/500/150/450/5/50	500	150	160	160	136	50	5.700
VUHD/500/200/450/5/80	500	200	210	210	197	80	8.000
VUHD/600/150/550/5/80	600	150	160	160	203	80	8.000
VUHD/600/200/550/5/80	600	200	210	210	199	870	10.000

25.4 mm = 1 inch 1 kg = 2.2 lbs

VULKOLLAN® HEAVY-DUTY DRIVE WHEELS

EURO (MM) DIMENSIONS



VUHD H7 SERIES

VULKOLLAN®
heavy-duty drive wheels
Stable welded wheel center
with bore and keyway
according to DIN 6885.
Direct bonded VULKOLLAN®
tread (93° Shore A).

Item #	Diameter (mm)	Wheel Width (mm)	Hub Length (mm)	Hub Diameter (mm)	Bore Dia. (mm)	Load Capacity (kg)
VUHD/300/075/260/2/50 H7	300	75	85	96	50	2.000
VUHD/300/100/260/2/60 H7	300	100	110	116	60	2.500
VUHD/360/075/310/2/70 H7	360	75	85	116	70	2.500
VUHD/360/100/310/2/60 H7	360	100	110	116	60	3.000
VUHD/400/100/350/2/70 H7	400	100	110	121	70	3.500
VUHD/400/120/350/2/60 H7	400	120	130	116	60	4.000
VUHD/400/120/350/2/70 H7	400	120	130	116	70	4.000
VUHD/400/150/350/2/60 H7	400	150	160	117	60	5.500
VUHD/500/100/450/2/60 H7	500	100	110	116	60	4.500
VUHD/500/150/450/2/80 H7	500	150	160	136	80	5.700
VUHD/500/200/450/2/80 H7	500	200	210	135	80	8.000
VUHD/600/150/550/2/80 H7	600	150	160	116	80	8.250
VUHD/600/200/550/2/80 H7	600	200	210	135	80	10.000
VUHD/700/200/640/2/80 H7	700	200	210	136	80	11.500

25.4 mm = 1 inch 1 kg = 2.2 lbs

VULKOLLAN® heavy-duty drive wheels with connecting bore hold or for the reception of clamping sets available on request.

Diameter H7 Bore from (mm)	Diameter H7 Bore to (mm)	Keyway width x height
13	17	5 x 2.3
18	22	6 x 2.8
23	30	8 x 3.3
31	38	10 x 3.3
39	44	12 x 3.3
45	50	14 x 3.8
51	58	16 x 4.3
59	65	18 x 4.4
66	75	20 x 4.9
76	85	22 x 5.4
86	95	25 x 5.4
96	110	28 x 6.4
111	130	32 x 7.4