

MAXROK™ V-GROOVE - MV

Capacity Up to 800 lbs.



Features

- Injection molded ultra-strong, glass filled nylon wheel has the same weight capacity of steel, yet incredibly light-weight.
- Rust free material makes this the perfect wheel for outdoor applications.
- 100% washable & steam cleanable; not effected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength and abrasion and compression resistance.
- Durometer: 85 Shore D +/-5.
- Temperature range: -45°F to +250°F.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Precision Ball Bearings*	Part Number
4	2	2-3/16	800	60, 6S	MV40JT*

Replace* with desired bearing code.

60 Sealed precision ball bearing (flanged) ID 1/2"

6S SS Sealed precision ball bearing (flanged) ID 1/2"

NYLON - NY

Capacity Up to 1100 lbs.



Features

- Solid wheel molded from Nylon 6.
- 100% washable & steam cleanable; impervious to water, highly resistant to organic solvents, most chemicals & cleaning solutions; ideal for use in food processing and packaging plants.
- Offers high impact strength and exceptional abrasion resistance.
- Hard tread has slight crown and rolls very easily.
- Non-marking.
- Durometer: 75 Shore A +/-5.
- Temperature range: -40°F to +210°F.

Diameter (inch)	Width (inch)	Hub Length	Capacity (lbs)	Ball Bearings*	Part Number
4	2	2-3/16	800	60, 6S, 72	NY40JE*
5	2	2-3/16	900	60, 6S, 72	NY50JE*
6	2	2-3/16	1000	60, 6S, 72	NY60JE*
8	2	2-3/16	1100	60, 6S, 72	NY80JE*

Replace* with desired bearing code.

60 Sealed precision ball bearing (flanged) ID 1/2"

6S SS Sealed precision ball bearing (flanged) ID 1/2"

72 SS Sealed precision ball bearing (w/top hats) ID 1/2"