

# VULKOLLAN® PRESS-ON TIRES

## EURO (MM) DIMENSIONS



VUZ SERIES

Item #	Flange Diameter (D mm)	Tread Width (W mm)	Inner Diameter (d mm)	Load Capacity (kg)
VUZ/100/032/075	100	32	75	280
VUZ/100/043/055	100	43	55	390
VUZ/100/070/055	100	70	55	600
VUZ/125/040/075	125	40	75	420
VUZ/125/050/075	125	50	75	540
VUZ/150/040/100	150	40	100	520
VUZ/150/050/100	150	50	100	640
VUZ/150/065/100	150	65	100	820
VUZ/150/075/100	150	75	100	960
VUZ/150/100/085	150	100	85	1.260
VUZ/150/130/100	150	130	100	1.640
VUZ/160/050/100	160	50	100	730
VUZ/160/075/100	160	75	100	1.020
VUZ/180/050/120	180	50	120	760
VUZ/180/075/120	180	75	120	1.140
VUZ/180/100/105	180	100	105	1.520
VUZ/200/050/140	200	50	140	840
VUZ/200/060/150	200	60	150	1.020
VUZ/200/070/140	200	70	140	1.180
VUZ/200/075/100	200	75	100	1.370
VUZ/200/080/120	200	80	120	1.360
VUZ/200/085/105	200	85	105	1.440
VUZ/200/105/120	200	105	120	1.780
VUZ/230/050/170	230	50	170	980
VUZ/230/075/170	230	75	170	1.460
VUZ/230/085/170	230	85	170	1.660
VUZ/250/050/190	250	50	190	1.060
VUZ/250/060/190	250	60	190	1.260
VUZ/250/075/140	250	75	140	1.580
VUZ/250/080/170	250	80	170	1.680
VUZ/250/100/170	250	100	170	2.100
VUZ/250/105/170	250	105	170	2.220
VUZ/250/105/190	250	105	190	2.220
VUZ/250/130/140	250	130	140	2.740
VUZ/254/076/203	254,0 (10")	76,0 (3")	203,0 (8")	1.640
VUZ/254/102/165	254,0 (10")	102,0 (4")	165,0 (6-1/2")	2.180
VUZ/254/127/165	254,0 (10")	127,0 (5")	165,0 (6-1/2")	2.720
VUZ/260/085/170	260	85	170	1.860
VUZ/260/105/170	260	105	170	2.300
VUZ/267/089/203	267,0 (10-1/2")	89,0 (3-1/2")	203,0 (8")	2.000
VUZ/285/075/220	285	75	220	1.800
VUZ/285/100/200	285	100	200	2.400
VUZ/285/100/220	285	100	120	2.400
VUZ/285/100/228	285	100	228	2.400
VUZ/290/105/185	290	105	185	2.560
VUZ/300/050/240	300	50	240	1.260
VUZ/300/075/240	300	75	240	1.800

25.4 mm = 1 inch 1 kg = 2.2 lbs

**VULKOLLAN®**  
press-on tires  
Cylindrical VULKOLLAN®  
press-on tires (93° Shore A)  
with machined steel band  
for rims with fit h11.

# VULKOLLAN® PRESS-ON TIRES

## EURO (MM) DIMENSIONS



VUZ SERIES

Item #	Flange Diameter (D mm)	Tread Width (W mm)	Inner Diameter (d mm)	Load Capacity (kg)
VUZ/300/090/203	300	90	203	2.160
VUZ/300/100/203	300	100	203	2.750
VUZ/310/060/220	310	60	220	1.480
VUZ/310/120/203	310	120	203	2.980
VUZ/310/120/220	310	120	220	2.980
VUZ/330/089/203	330,0 (13")	89,0 (3-1/2")	203,0 (8")	2.100
VUZ/330/089/254	330,0 (13")	89,0 (3-1/2")	254,0 (10")	2.350
VUZ/330/127/254	330,0 (13")	127,0 (5")	254,0 (10")	3.350
VUZ/330/145/193,5	330	145	193,5	3.820
VUZ/343/114/225	343	114	225	3.120
VUZ/345/115/245	345	115	245	3.340
VUZ/350/090/280	350	90	280	2.600
VUZ/350/100/280	350	100	280	2.800
VUZ/350/110/270	350	110	270	3.080
VUZT/350/140/270	350	140	270	3.920
VUZ/360/075/270	360	75	270	2.470
VUZ/360/085/270	360	85	270	2.450
VUZ/381/127/286	381,0 (15")	127,0 (5")	286,0 (11-1/4")	3.860
VUZ/400/075/305	400	75	305	2.750
VUZ/405/065/305	405	65	305	2.100
VUZ/405/130/290	405	130	290	3.800
VUZ/405/130/305	405	130	305	4.000
VUZ/405/145/290	405	145	290	4.100
VUZ/406/178/305	406	178	305	5.400
VUZ/415/075/305	415	75	305	2.500
VUZ/415/090/305	415	90	305	3.000
VUZ/415/100/305	415	100	305	3.370
VUZ/445/178/381	445,0 (17-1/2")	178,0 (7")	381,0 (15")	6.000
VUZ/457/127/308	457,0 (18")	127,0 (5")	308,0 (12-1/4")	4.650
VUZ/457/152/308	457,0 (18")	152,0 (6")	308,0 (12-1/4")	4.950
VUZ/457/178/308	457,0 (18")	178,0 (7")	308,0 (12-1/4")	5.400
VUZ/500/085/370	500	85	370	3.000
VUZ/500/100/370	500	100	370	3.660
VUZ/500/140/370	500	140	370	5.130
VUZ/559/152/406	559,0 (22")	152,0 (6")	406,0 (16")	5.950
VUZ/559/203/406	559,0 (22")	203,0 (8")	406,0 (16")	8.000
VUZ/559/229/406	559,0 (22")	229,0 (9")	406,0 (16")	8.950
VUZ/610/150/410	610	150	410	6.400
VUZ/645/250/500	645	250	500	2.300
VUZ/660/127/508	660,0 (26")	127,0 (5")	508,0 (20")	6.550
VUZ/711/203/559	711,0 (28")	203,0 (8")	559, 0 (22")	10.100
VUZ/711/254/559	711,0 (28")	254,0 (10")	559, 0 (22")	12.650
VUZ/711/305/559	711,0 (28")	305,0 (12")	559, 0 (22")	15.200
VUZ/750/150/640	750	150	640	7.880
VUZ/900/200/670	900	200	670	12.600
VUZ/920/180/770 U9	920	180	770	11.600
VUZ/920/290/770	920	290	770	18.500

25.4 mm = 1 inch 1 kg = 2.2 lbs