

XTRA-SOFT ROUND GREY TREAD - XR

Capacity Up to 600 lbs.



Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Part Number*
6	2	450	2-7/16	1-3/16	1/2	2-1/4	XR0622808
8	2	600	2-7/16	1-3/16	1/2	3-1/2	XR0822808

The Ultimate Xtra soft rubber wheels offer the ultimate in ergonomic ease. Whether it's durability, quiet operation, or rollability, these wheels can answer your every application need.

Wheel Options

- Prevenz™ Antimicrobial wheel available specify **PREV.**

Features

- **Wheel Face:** Round tread.
- **Finish:** Non-marking gray tread on gray core.
- **Temperature Range:** -45°F up to +180°F.
- **Hardness:** 65-75 Shore A.

Precision Ball Bearing (28)

ULTIMATE X-TRA SOFT RUBBER

XTRA SOFT RUBBER/ POLYPROPYLENE CORE/ DONUT TREAD - XS

Capacity Up to 850lbs.



The Ultimate Xtra soft rubber wheels offer the ultimate in ergonomic ease. Whether it's durability, quiet operation, or rollability, these wheels can answer our every application need.

Features

- **Wheel Face:** XS: Moderate Crown.
- **Finish:** Non-marking gray tread on gray core.
- **Wheels:** Non-marking black tread on gray core.
- **Temperature Range:** -45°F up to +180°F.
- **Hardness:** 65-75 Shore A.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Wheel Bearing	Part Number
Xtra-Soft Flat Gray Tread (Medium Heavy Duty)								
4	2	350	2-3/16	1-3/16	3/4	1	Delrin	XS0425112
4	2	350	2-3/16	1-3/16	3/4	1	Roller	XS0420112
4	2	350	2-7/16	1-9/16	1/2	1	Precision Ball	XS0422808
5	2	375	2-3/16	1-3/16	3/4	1-1/8	Delrin	XS0525112
5	2	375	2-3/16	1-3/16	3/4	1-1/8	Roller	XS0520112
5	2	375	2-7/16	1-9/16	1/2	1-1/8	Precision Ball	XS0522808
6	2	600	2-3/16	1-3/16	3/4	1-3/8	Delrin	XS0625112
6	2	600	2-3/16	1-3/16	3/4	1-3/8	Roller	XS0620112
6	2	500	2-7/16	1-9/16	1/2	1-3/8	Precision Ball	XS0622808
8	2	675	2-3/16	1-3/16	3/4	2-3/8	Delrin	XS0825112
8	2	675	2-3/16	1-3/16	3/4	2-3/8	Roller	XS0820112
8	2	500	2-7/16	1-9/16	1/2	2-3/8	Precision Ball	XS0822808
Xtra-Soft (Medium Heavy Duty Conductive)								
4	2	350	2-3/16	1-3/16	3/4	1	Roller	XY0420112
4	2	350	2-7/16	1-9/16	1/2	1	Precision Ball	XY0422808
5	2	375	2-3/16	1-3/16	3/4	1-1/8	Roller	XY0520112
5	2	375	2-7/16	1-9/16	1/2	1-1/8	Precision Ball	XY0522808
6	2	600	2-3/16	1-3/16	3/4	1-3/8	Roller	XY0620112
6	2	500	2-7/16	1-9/16	1/2	1-3/8	Precision Ball	XY0622808
8	2	675	2-3/16	1-3/16	3/4	2-3/8	Roller	XY0820112
8	2	500	2-7/16	1-9/16	1/2	2-3/8	Precision Ball	XY0822808

Wheel Options: Prevenz™ Antimicrobial wheel available specify **PREV.**

ULTIMATE X-TRA SOFT RUBBER

XTRA SOFT RUBBER/ POLYPROPYLENE CORE/ DONUT TREAD - XR

Capacity Up to 850lbs.



The Ultimate Xtra soft rubber wheels offer the ultimate in ergonomic ease. Whether it's durability, quiet operation, or rollability, these wheels can answer our every application need.

Features

- **Wheel Face:** Round tread.
- **Finish:** Non-marking gray tread on gray core.
- **Wheels:** Non-marking black tread on gray core.
- **Temperature Range:** -45°F up to +180°F.
- **Hardness:** 65-75 Shore A.

Dia. (inch)	Width (inch)	Capacity (lbs)	Hub Length (inch)	Bore (inch)	Bearing (inch)	Wt. (lbs)	Wheel Bearing	Part Number
Xtra-Soft Round Gray Tread (Medium Heavy Duty)								
6	2	450	2-3/16	1-3/16	3/4	1-3/8	Delrin	XR0625112
6	2	450	2-3/16	1-3/16	3/4	1-3/8	Roller	XR0620112
6	2	450	2-7/16	1-9/16	1/2	1-3/8	Precision Ball	XR0622808
8	2	600	2-3/16	1-3/16	3/4	2-3/8	Delrin	XR0825112
8	2	600	2-3/16	1-3/16	3/4	2-3/8	Roller	XR0820112
8	2	500	2-7/16	1-9/16	1/2	2-3/8	Precision Ball	XR0822808
Xtra-Soft Round Black Tread (Hand Truck Offset Hub)								
8	2	250	2-1/4	1-3/8	1/2	2	Industrial Ball	XR0822708H
8	2	250	2-1/4	1-3/8	5/8	2	Industrial Ball	XR0822710H
8	2	250	2-1/4	1-3/8	1/2	2	Precision Ball	XR0822808H
8	2	250	2-1/4	1-3/8	5/8	2	Precision Ball	XR0822810H
10	2	250	2-1/4	1-3/8	1/2	2	Industrial Ball	XR1022708H
10	2	250	2-1/4	1-3/8	5/8	2	Industrial Ball	XR1022710H
10	2	250	2-1/4	1-3/8	1/2	2	Precision Ball	XR1022808H
10	2	250	2-1/4	1-3/8	5/8	2	Precision Ball	XR1022810H
Xtra-Soft Round Conductive								
6	2	450	2-3/16	1-3/16	3/8	1-3/8	Annular Ball	XZ0623106
6	2	450	2-3/16	1-3/16	3/4	1-3/8	Roller	XZ0620112
6	2	450	2-7/16	1-9/16	1/2	1-3/8	Precision	XZ0622808
8	2	600	2-3/16	1-3/16	3/8	2-3/8	Annular Ball	XZ0823106
8	2	600	2-3/16	1-3/16	3/4	2-3/8	Roller	XZ0820112
8	2	600	2-7/16	1-9/16	1/2	2-3/8	Precision	XZ0822808

Wheel Options: Prevenz™ Antimicrobial wheel available specify **PREV.**